

Saunaofen Herkules S60 vapor

For commercial sauna

Free standing heater

Outer shell:

The exterior design features a striking combination of straight lines, massive yet elegant steel with the raw sauna rocks.

The internal and external shell is completely made of the best quality stainless steel.

Water container:

for approx. 8 litres

Terminal box:

high-grade steel

Stone filling:

60 kg incl.

Service friendly unit assembly system


The heating elements are mounted on a rack and may be conveniently removed without the need to remove the rocks.

Optimised ratio of radiated heat and convection due to the appropriate amount of stones.




CE **DVE** **IP X4**
MADE IN GERMANY


Connection diagram



9 kW



12 - 15 kW



Capacity acc. DIN	Vaporiser	Electrical Connection	Fuse control unit in A	Fuse LSG in A	Connecting cable main - control unit in mm²	Connecting cable main - LSG in mm²	Connecting cable control unit - heater in mm²	Connecting cable LSG - heater in mm²	Connecting cable control unit - LSG in mm²
9,0 kW	2,0 kW	3N AC 50 Hz 400 V	3 x 16	--	5 x 2,5	--	5 x 1,5 & 4 x 1,5	--	--
12,0 kW				3 x 16		5 x 2,5		5 x 1,5	4 x 1,5
15,0 kW				3 x 16		5 x 2,5		5 x 1,5	4 x 1,5

All cross sections of a line are minimum diameters in mm² (Copper line)

Art.-No.	Outer shell	Capacity acc. DIN	Vaporicer	Installation dimensions H/W/D cm	For cabin size	Minimum dimensions of air intake and exhaust vents	Weight without stones without package	Stone filling	Power switch gear (LSG) needed	For operation with control units
94.4494	Grinded stainless steel / anthracite	9,0 kW	2,0 kW 8 l	85 / 53 / 53	9 - 14 m³	35 x 6 cm	53 kg	60 kg	--	EMOTEC HCS 9003 EMOTEC HCS 9003 DB/DL/ DLF EmoTouch II PB/AF/GF
94.4270		12,0 kW			14 - 18 m³	35 x 7 cm			EMOTEC L09	
94.4271		15,0 kW			18 - 25 m³	35 x 9 cm				

Subject to technical modifications